

RECEIVED  
CENTRAL FAX CENTER

JUL 06 2007

In the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (currently amended) An universal joint hinge (10) for the articulation of a door leaf (12) on a carcass of a piece of furniture, the universal joint hinge comprising  
a mounting plate (18) designed to be disposed on a supporting wall (14) of the carcass on which and formed as an elongated support arm  
a carcass mounting part (16) is mounted [[.]] on the carcass mounting plate (16) is constructed as an elongated support arm,  
a universal joint mechanism comprising two joint arms (22; 24),  
a door leaf mounting part (20), constructed as a hinge cup, is disposed on a door leaf, wherein the a universal joint mechanism having two joint arms (22; 24) are pivitably pivotably connected to each other in their centers like scissors and each joint arm is pivotable at one of its ends about a fixed axis on one of the mounting parts (16; 20) and at the respective other end is attached to the respective other mounting part (20; 16) so as to be variable in position along a predetermined space curve extending in a plane lying at right angles to the pivot axis of the hinge,  
wherein the joint arm (24) is pivitably pivotably mounted about a fixed axis on or in the door leaf mounting part (20) at its opposite end coupled to the carcass mounting part (16) so as to be pivotable about a fixed axis on or in the end region of the carcass mounting part (16) inside the carcass,  
and wherein a portion of the joint arm (24a) which is positioned between the region which is pivotably mounted on the carcass mounting part (16) and the region which supports the joints arms (22; 24) so that the joints arms (22, 24) pivot approximately centrally like scissors comprising two joint arm portions (24a; 24b) which are longitudinally displaceable relative to one another by a predetermined amount, and  
wherein a damping device, which is effective at least during a part of a displacement movement of the joint arm portions relative to one another is provided between the two joint arm portions

(24a; 24b) and wherein the joint arm portions (24a; 24b) which are displaceable relative to one another, are advantageously constructed so that they engage telescopically.

2. (canceled)

3. (previously presented) The universal joint hinge as claimed in Claim 1, wherein one joint arm portion (24b) is formed by an elongated cylinder which is disposed so as to be longitudinally displaceable on a piston rod which forms the other joint arm portion..

4. (previously presented) The universal joint hinge as claimed in Claim 3, wherein the piston rod (24a) is attached integrally on the central region pivotably coupled in scissor fashion to the other joint arm (22), and the cylinder (24b) which is disposed so as to be longitudinally displaceable on the piston rod (24a) is articulated with its end facing away from the inlet side of the piston rod (24a) so that it is pivotable on the carcass mounting part (16).

5. (currently amended) The universal ~~Universal~~ joint hinge as claimed in Claim 4, wherein the end of the cylinder (24b) which is articulated on the carcass mounting part (16) is closed.

6. (currently amended) The universal ~~Universal~~ joint hinge as claimed in Claim 3, wherein a piston of which the diameter is substantially equal to the internal diameter of the cylinder (24b) is mounted on the free end of the piston rod (24b), and that the interior of the cylinder is divided into two working spaces which are separated from one another by the piston and vary in volume in opposite directions in the case of a relative displacement of the piston rod (24a) and the cylinder (24b), and in which a fluid damping medium is provided.

7. (currently amended) The universal Universal joint hinge as claimed in Claim 3, wherein the cylinder (24b) is integrally attached on the central region pivotably coupled in scissor fashion to the other joint arm (22), and that the piston rod (24a) which is disposed so as to be longitudinally displaceable in the cylinder (24b) is pivotably articulated on the carcass mounting part (16) at the free end thereof lying opposite the inlet side into the cylinder (24b).

8. (currently amended) The universal ~~Universal~~ joint hinge as claimed in Claim 3,

wherein the aligned longitudinal central axes of the cylinder (24b) and of the piston rod (24a) lie in the longitudinal central plane of the hinge (10) extending at right angles to the pivot axis of the hinge.

9. (currently amended) The universal ~~Universal~~ joint hinge as claimed in Claim 3, wherein the aligned longitudinal central axes of the cylinder (24b) and of the piston (24a) are disposed in a plane offset laterally from and parallel to the longitudinal central plane of the hinge (10).

10. (currently amended) The universal ~~Universal~~ joint hinge as claimed in Claim 9, wherein in a second plane offset parallel to the opposing side of the longitudinal central plane of the hinge the aligned longitudinal central axes of a second cylinder (24b) provided there and of a second piston rod (24a) are disposed.